



**ABRASION
RESISTANT PLUS**



**"COLD-FLEX"
MATERIALS**



**OIL
RESISTANT**



**STATIC
DISSIPATIVE**



Ureflex™

UF2™ Series

Extra Heavy Duty Polyurethane Lined Material Handling Hose

General Applications:

- Fly ash collection
- Industrial vacuum equipment
- Material chutes
- Material handling – heavy duty abrasive
- Milling machine scrap recovery
- Rock, gravel, sand and crushed concrete vacuuming
- Shot blast recovery

Construction: PVC cover with polyurethane liner and rigid PVC helix.

Service Temperature: -40°F (-40°C) to 150°F (+65°C)*

Features and Advantages:

- **Extra Thick Abrasion Resistant Polyurethane Liner** – Designed for dry applications where severe abrasion is a factor. Provides for longer hose life and lower operating costs versus rubber or PVC hoses.
- **Static Dissipative Cover** – Specially formulated to help prevent the build-up of static electricity for added safety and to help keep material flowing smoothly.
- **"Cold-Flex" Materials** – Hose remains flexible in sub-zero temperatures.
- **Convuluted Outer Cover** – Provides increased hose flexibility.
- **Oil Resistant Polyurethane Liner** – Resists most animal and petroleum based oils.

Nominal Specifications

Series	ID (in.)	ID (mm)	OD (in.)	OD (mm)	Working Pressure (psi)		Vacuum Rating (in. Hg)		Min. Bending Radius (in. @ 68°F)	Standard Length (ft.)	Weight (lbs./ft.)
					68°F	104°F	68°F	104°F			
UF2-150	1½	38.1	1.88	47.8	50	25	Full	28	3	100	0.46
UF2-200	2	50.8	2.44	62.0	40	20	Full	28	4	100	0.65
UF2-250	2½	63.5	3.12	79.2	40	20	Full	28	5	100	0.89
UF2-300	3	76.2	3.70	94.1	40	20	Full	28	6	100/50	1.23
UF2-400	4	101.6	4.80	122.0	35	18	Full	28	10	100/50	2.02
UF2-500	5	127.0	5.81	147.6	35	18	28	25	15	100/50/20	2.50
UF2-600	6	152.4	6.87	174.5	30	15	28	25	18	100/50/20	3.84
UF2-800	8	203.2	9.18	233.2	30	15	28	25	22	50/20	6.52
UF2-1000	10	254.0	11.61	295.0	25	12	26	20	26	20	10.92

NOTE: Service life may vary depending on operating conditions and type of material being conveyed.

NOTE: For details of the following compliances, refer to footnotes listed on page 62.

*Actual service temperature range is application dependent.

RoHS(11)

Because we continually examine ways to improve our products, we reserve the right to alter specifications or discontinue products without prior notice.

KTFCOA0116